

Code & Name	LAM-FM/Flooring Graphic Lamination Matte									
Features	200mic rough embossed textured film; 140gsm paper liner; CSIRO Slip Rating: R10 ; Protect floor graphics against abrasion, scratch and constant surface contact									
Applications	Banners, Signs, Flags	Large Billboard /Frame	Adhesive Signages	POP Displays posters	Backlit Displays / frames	Exhibits, Events signs	Vehicle Graphic	Window Graphic	Arts-graphic/ Photo-graphic reproduction	Magnetic Signs
				■						
Sizes	1270/1520mm X50m									
Physical Properties	Face film	Monomeric calendered rough embossed textured vinyl film								
	Finish	Extra Matte								
	Whiteness	90.57								
	Brightness	8.3								
Adhesive & Release Liner Properties	Liner type	140g/m ² PE Paper								
	Adhesive thickness	24mic Acrylic Permanent Clear								
	Initial Tack(30° slope device)	≥4#								
	Holding : 9.8N on 1 square foot	≥ 8hours								
	180° Peeling strength	6N/2.5CM								
Storage & Application	Shelf Time	12 Months								
	Application Temperature	5~40℃								
	Durability	Up to 1 year								

■ FULLY COMPATIBLE

□ FAIRLY COMPATIBLE OR NEED TO BE VERIFIED.

Note: All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the "information") shall be provided only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. We shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the information.

NuConCept

be used
re
istics
reliance